

## Handle with integrated hader click® 2.0 – 4.0 Nm



This patented device (CH patent number 698 913) is engineered to provide repeatable and precise performance. The hader click® torque limiter emits an audible **click** when the desired torque value is reached.

<b>Product</b>	<b>handle with hader click 2.0-4.0</b>
<b>Choice of torque value</b>	one fixed torque value, according to request, between 2.0 - 4.0 Nm
<b>Coupling male / female</b>	AO female, blade according to request
<b>Working range</b>	works clockwise (click)
<b>Max admissible torque anti-clockwise</b>	3 x nominal torque (no click)
<b>Torque precision</b>	± 10%
<b>Possibility of canulation</b>	yes, Ø2.2mm
<b>Material</b>	stainless steel and medical grade plastic
<b>Laser marking</b>	yes, on request
<b>Dismantle before cleaning</b>	no
<b>Maintenance</b>	no maintenance, no grease applied inside, no recalibration within guarantee
<b>Autoclave sterilisation</b>	134°C /18 min or 273°F /18 min
<b>Weight (gram)</b>	about 240
<b>Packaging</b>	plastic tube
<b>Instructions for use</b>	yes
<b>Feature</b>	available without torque limiter
<b>Remarks</b>	Maximum torque on the bearing given by a radial force : $M = 0.3Nm$

